

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Reference nr: 230211

Unique identification code of the product-type

Fix ALL Turbo

Intended use or uses of the construction product

Sealants for facade for interior application

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

System 3: for reaction to fire

System 4: for essential characteristics

Construction product in accordance with applicable harmonised specifications

EN 15651-1:2012: Type F-INT

The notified body

The notified body WFR GENT, NB 1173 has carried out Determination of the Product Type under system 3 for reaction to fire.



Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning: Method A

Test Substrate: aluminium, mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011



NB 1173

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr: 230211

EN 15651-1:2012

Sealants for facade for interior application

Fix ALL Turbo

EN 15651-1:2012: Type F-INT

Conditioning: Method A

Test Substrate: aluminium, mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	≥ 25%	
Durability	Pass	



UKCA Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

UK Reference nr DOP: 230211UK

Unique identification code of the product-type

Fix ALL Turbo

Intended use or uses of the construction product

Sealants for facade for interior application

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative

**Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth
B77 5PN Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

System 3: for reaction to fire

System 4: for essential characteristics

Construction product in accordance with applicable designated standards

BS EN 15651-1:2012: Type F-INT

Approved Body

**Warringtonfire Testing and Certification Limited, AB 0833, has carried out Determination of the
Product Type under system 3.**



Declared Performance: BS EN 15651-1:2012

Essential Characteristics	Performance	Designated Technical Specification
Release dangerous chemicals	NPD	BS EN 15651-1:2012
Resistance to flow	≤ 3 mm	
Water and air tightness		
Loss of volume	NPD	
Elongation at break	NPD	
Durability	Pass	

Conditioning: Method A

Test substrate: aluminium, mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

**UK
CA**
AB 0833

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

21

UK Reference nr DOP: 230211UK

BS EN 15651-1:2012

Sealants for facade for interior application

Fix ALL Turbo

BS EN 15651-1:2012: Type F-INT

Conditioning: Method A

Test substrate: aluminium, mortar

Essential Characteristics	Performance	Designated Technical Specification
Release dangerous chemicals	NPD	BS EN 15651-1:2012
Resistance to flow	≤ 3 mm	
Water and air tightness		
Loss of volume	NPD	
Elongation at break	NPD	
Durability	Pass	